





Telebelt® TB 110 Specifications

Conveyors		
Conveyor horizontal reach		
Maximum at 0°	106' 1"	(32.34m)
Maximum at 30°	91' 6"	(27.91m)
Conveyor belt width	18"	(457mm)
Feed conveyor length	38' 0"	(11.60m)
Feed conveyor belt width	18"	(457mm)
Trunk/end hose length	15' 0"	(4.57m)
Discharge height from grade		
Maximum at 30°	60' 2"	(18.36m)
Maximum at -15°	-20' 0"	(-6.11m)
Main & feed conveyors		
Observed capacity at 0°	5.00 yd³/min	(4.00m ³ /min)
Observed capacity at 20°	5.00 yd³/min	(4.00m ³ /min)

Outriggers		
Net reach beyond outriggers —		
at 0°	100' 6"	(30.65m)
at 30°	86' 0"	(26.23m)
Outrigger spread L-R — front manual out, hydraulic extended down	23' 1"	(7.05m)
Outrigger spread L-R — rear manual out, hydraulic extended down	26' 9"	(8.17m)
Outrigger spread front to rear	27' 5"	(8.37m)

General Specifications		
Water tank capacity	200 gal	(757 L)
Hydraulic oil tank capacity (with cooler)	150 gal	(568L)

Truck Specifications *•+		
Weight	20,525 lbs	(9,310kg)
Engine horsepower	405 hp	(302kW)
Wheelbase	299"	(7,595mm)
Cab height	104"	(2,642mm)
Steering radius (outside)	45' 6"	(13.87m)
Steering angle	30°	
Fuel tank capacity	80 gal	(303L)
Transmission	Mack T310 10-Speed	

Transport Axle Weights *•+		
Steering	19,008 lbs	(8,621kg)
Pusher	10,000 lbs	(4,535kg)
Tandem	33,754 lbs	(15,309kg)
Total	62,762 lbs	(28,465kg)

Maximum theoretical values listed.

- * Truck dimensions will vary with different truck makes, models and specifications.
- Weights are approximate and include truck, fuel, and 100 gal (379L) of water.
- + All specifications apply to units mounted on Mack MRU 613.





Putzmeister America, Inc. 1733 90th Street Sturtevant. WI 53177 USA Phone Toll-free Fax (262) 886-3200 (800) 884-7210 (262) 884-6338